

**International Corporate Headquarters**  
Tel: +972 3 645 6262  
Fax: +972 3 645 6222  
Email: corporate-sales@alvarion.com

**North America Headquarters**  
Tel: +1 760 517 3100  
Fax: +1 760 517 3200  
Email: n.america-sales@alvarion.com

**Latin America & Caribbean**  
Tel: +1 954 746 7420  
Fax: +1 954 746 9332  
Email: lasales@alvarion.com

**Brazil**  
Tel: +55 11 3815 6225  
Fax: +55 11 3813 0467  
Email: brazil-sales@alvarion.com

**China**  
Tel: +86 10 8857 6770  
Fax: +86 10 8857 6772  
Email: china-sales@alvarion.com

**Czech Republic**  
Tel: +420 222 191 233  
Fax: +420 222 191 200  
Email: czech-sales@alvarion.com

**France**  
Tel: +33 1 34 38 54 30  
Fax: +33 1 34 38 54 39  
Email: france-sales@alvarion.com

**Germany**  
Tel: +49 89 90405 923  
Fax: +49 89 90405 922  
Email: germany-sales@alvarion.com

**Japan**  
Tel: +81 3 3761 7206  
Fax: +81 3 3761 7208  
Email: alvarion-japan@alvarion.com

**Mexico**  
Tel: +52 555 340 1421  
Fax: +52 555 340 1403  
Email: mexico-sales@alvarion.com

**Romania**  
Tel: +40 21 335 7631  
Fax: +40 21 335 7634  
Email: romania-sales@alvarion.com

**Russia**  
Tel: +7 (095) 783 82 31  
Fax: +7 (095) 287 98 99  
Email: info@alvarion.ru

**U.K. & Ireland**  
Tel: +44 845 450 1414  
Fax: +44 845 450 1455  
Email: uk-sales@alvarion.com

**Uruguay**  
Tel: +598 2 606 2651  
Fax: +598 2 606 2652  
Email: lasales@alvarion.com

© Copyright 2004 Alvarion Ltd. All rights reserved.  
Alvarion, BreezeCOM, WALKair, WALKnet, BreezeNET, BreezeMANAGE, BreezeACCESS, BreezeLINK, BreezePHONE, MGW, eMGW and/or other products and/or services referenced here in are either registered trademarks, tradenames or service marks of Alvarion Ltd.  
All other names are or may be the trademarks of their respective owners.  
The content herein is subject to change without further notice.



www.alvarion-usa.com

## Specifications

### Radio

Frequency	5.725-5.850 GHz, 5.47-5.725GHz*	
Radio type	OFDM, TDD	
Channel bandwidth	20 MHz	
Center frequency resolution	10 MHz	
Output power (at antenna port)	Up to 21 dBm	
Modulation	BPSK, QPSK, 16QAM, 64QAM	
Sensitivity	-89 dBm at BPSK	
	-86 dBm at QPSK	
	-81 dBm at 16-QAM	
	-71 dBm at 64-QAM	
Antenna	BU and RB	23 dBi, 9" V/H, Flat Panel
	Detached antennas	28 dBi, 4.5" V/H, Flat Panel, 31 dBi, 4.2" V/H, Parabolic
Antenna port (Detached model)	N Type, 50 Ohm	

### Data Communication

Standard compliance	IEEE 802.3 CSMA/CD
VLAN support	Based on 802.1q
Security	a. Association protocol - ESSID
	b. WEP 128, AES
	c. IP level filtering for user addresses or protocols
	d. Access direction and IP address filtering for management

### Configuration and Management

Configuration and management	Via Telnet, SNMP, TFTP SNMP based configuration utility
Remote management access	From wired LAN, wireless link
Management access protection	Multilevel password
	Configuration of remote access direction (from Ethernet only, from wireless link only or from both sides)
	Configuration of IP addresses of authorized stations
Allocation of IP parameters	Configurable or automatic (DHCP client)
Software upgrade and configuration	FTP/TFTP download
SNMP agent	SNMP V1 Client, MIB II, Bridge MIB, Private BreezeNET B MIB

### Electrical Characteristics - RB and BU

Power consumption	25W	
Input power	AC, 100-240 VAC, 50-60 Hz	
Indoor outdoor cable	CAT-5 shielded, 300ft (90m) max	
Indicators	Indoor unit	Power, Link and Ethernet LEDs
	Outdoor unit	Status, Ethernet and W-Link LEDs SNR 10 LEDs bar indicator (RB only)
Connectors	Data	RJ-45 10/100 BaseT Auto Sense
	AC Power	3 pin AC power plug (indoor unit only)

### Physical and Environmental

Dimensions - RB and BU	Indoor unit	6.3 in x 3.5 in x 2.4 in (16 x 9 x 6 cm) 1.2 lb (0.55 Kg)
	Outdoor unit	12 in x 4.7 in x 1.9 in (30.6 x 12 x 4.7 cm) 4.1 lb (1.85 Kg)
Operating temperature	Outdoor unit	-40°F to 131°F (-40°C to 55°C)
	Indoor unit	32°F to 104°F (0°C to 40°C)
Operating humidity	Outdoor unit	5%-95% non condensing, weather protected
	Indoor unit	5%-95% non condensing

### Standards and Regulations

Radio	FCC part 15, ETSI EN 301 753, ETSI EN 301 021	
EMC	FCC part 15 class B, ETSI EN 489-1	
Safety	UL 1950, EN 60950	
Lightning protection	EN 61000-4-5, Class 3 (2kV)	
Environmental	Operation	ETS 300 019 part 2-3 class 3.2E for indoor unit ETS 300 019 part 2-4 class 4.1E for outdoor unit
	Transportation	ETS 300 019-2-2 class 2.3
Storage	ETS 300 019-2-1 class 1.2E	

\*Q2 2004



# BreezeNET B14

Taking PTP Wireless to a Higher Point of Efficiency

- Cost effective Ethernet bridging & backhauling
- OFDM technology
- Outdoor radio with extra long range
- Robust performance in NLOS environments
- Multi level data security protection
- Suitable for a wide range of Point-to-Point applications
- Unlicensed 5 GHz bands
- Simple installation and maintenance





## Product Highlights & Advantages

- **Cost effective alternative to leased lines with fast ROI**
- **Optimal cost/performance ratio: highly cost efficient solution**
- **Robust outdoor architecture: ensures unprecedented range and reliability**
- **Superior OFDM radio: enables Non Line Of Sight (NLOS) capabilities in dense urban environments**
- **Ideal for noisy environments: Adaptive Modulation and Forward Error Correction (FEC) features optimize performance**
- **High throughput: up to 7 Mbps simultaneous each direction**
- **Variety of frequencies: in the 5 GHz band**
- **Non-compromising Security: AES or 128 bit WEP key encryption (selectable)**
- **Easy to install and adjust: full LED diagnostics, 10-LED bar display for antenna alignment, user-friendly management tool application**
- **Simple to upgrade: update software and reconfigure settings over the air**
- **Built-in remote diagnostics: minimize maintenance costs and downtime**

### BreezeNET B14: The Optimal Point-to-Point Solution

The BreezeNET B14 is a wireless Point-to-Point bridging solution that operates in the unlicensed 5GHz band and provides an efficient and highly secured solution for building-to-building connectivity and backhauling. It is an ideal cost efficient alternative to expensive leased lines, providing an instant link for connecting remote local offices to headquarters, and isolated buildings on campuses and in industrial zones.

Moreover, ISPs can leverage BreezeNET B14 as a powerful and cost-effective wireless link to backhaul their Point-to-Multipoint data to their Internet access network, avoiding the need for expensive, leased lines over wire line infrastructures.

### Operating Beyond the Line of Sight

Alvarion developed the BreezeNET B14 in recognition of the need to provide a viable and cost-effective solution for dense urban and industrial environments where a clear line of sight for Point-to-Point applications is not always available. To that end, the BreezeNET B14 leverages both robust outdoor technologies and Orthogonal Frequency Division Multiplexing (OFDM) modulation in the same product. With features such as Forward Error Correction (FEC) coding, used to combat multi-path and noisy environments, the product operates seamlessly and efficiently in Non Line Of Sight (NLOS) environments with a relatively powerful throughput. The system also features adaptive modulation for automatic selection of modulation schemes to maximize the data rate and improve spectral efficiency. These inherent advantages of the BreezeNET B14 enable service providers to provide an effective PTP solution to a significantly higher subscriber base that would otherwise be inaccessible, due to LOS restrictions.

### Flexible Capacity for Differentiated Needs

The BreezeNET B14 system provides the option for flexible data rate configuration to meet a variety of Point-to-Point applications. Some operators selling T1 services can increase capacity either through a symmetrical or asymmetrical service configuration, offering data rates from 128Kbps to 7Mbps simultaneous in each direction.

### Highly Secured Air Interface

BreezeNET B14 supports security sensitive applications through the optional use of authentication and/or data encryption utilizing AES or WEP algorithms with 128 bit keys. The system also supports VLAN based on IEEE 802.1Q, facilitating secure operation and Virtual Private Network (VPN) services and enabling remote employees or offices to conveniently access their enterprise network.

### Built to Last

All BreezeNET B14 products are robust outdoor units that are built to perform in difficult climatic environments and withstand even the harshest weather conditions. Outdoor units typically maintain a significantly higher link budget than their indoor counterparts and therefore achieve higher performance and availability. Unlike Point-to-Point indoor units, which employ RF cables to run signals to rooftop antennas, outdoor units utilize a simple CAT-5 connection, which enables a significant reduction in the loss of power output levels. CAT-5 cables are also far easier to install and cost considerably less.

## BreezeNET B14 System Components

### Base Unit (BU)

The Base Unit (BU) is installed at one end of the PTP link and connects the link to a central server or to the Internet. The BU is composed of two parts, a universal Indoor Unit (IDU) and an Outdoor Unit (ODU). The main advantage of the product is that the radio and the signal processing are both in the outdoor unit; therefore, the B14 unit is a true outdoor device with no power loss associated with its indoor/outdoor cable.

### Remote Bridge (RB)

The RB is placed at the far end of the PTP link, connecting the end user to the centrally located BU. It is also composed of two parts, an identical universal indoor unit, like the one used in the BU, and an outdoor unit.

BreezeNET B14 BU/RB units come with a connector for easy connection to a detached external antenna, in which case it can be used with a 23 or 28 dBi flat panel antenna or a 31 dBi parabolic antenna for maximum performance in longer range links.

BU-B14 Base Unit	Connects directly to the 10/100 Base-T Ethernet backbone and links it to the central network point.
RB-B14 Remote Bridge	Connects directly to the 10/100 Base-T Ethernet LAN and links the remote Ethernet LAN to the central point via the Base Unit, servicing up to 1024 stations

